



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **05322699 A**(43) Date of publication of application: **07.12.93**

(51) Int. Cl.

G01M 11/00
H04B 10/08
(21) Application number: **04132904**(22) Date of filing: **25.05.92**(71) Applicant: **NIPPON TELEGR & TELEPH
CORP <NTT>**(72) Inventor: **SHIMIZU KAORU
HORIGUCHI TSUNEO
OYAMADA YAHEI**(54) **HIGH DISTANCE-RESOLUTION OPTICAL
TRANSMISSION LINE MEASURING DEVICE**

(57) Abstract:

PURPOSE: To achieve a high distance resolution by providing a ring resonator optical circuit in that a ring waveguide path which has the same loop length as light pulse length and where a gain medium is added and a frequency shifter are formed on a crystal substrate.

CONSTITUTION: An optical pulse modulator 2 converts irradiation light of a coherence light source 1 to an optical pulse with a specified pulse length. A synthesizer 3 synthesizes an excitation light from a light source 8 for excitation and that from the modulator 2 and then transmits it to a ring resonator optical circuit 4. The circuit 4 has an optical waveguide 44 and a ring waveguide 45 which has the same loop length as the incidence light pulse length and where a gain medium is added, a directional coupler 46 which connects the optical waveguide 44 and the waveguide 45, and a frequency shifter 47 which is inserted halfway through the waveguide 45 for shifting the frequency of a passage light on a crystal substrate 41, thus enabling an output light to be an equivalent continuous light which changes stepwise. Also, the loop length can be equal to 0.01mm, thus achieving a high

distance resolution. Also, light pulse loss can be compensated by the waveguide 45 and the shifter 47 and loss in the circuit 4 can be reduced to 0.

COPYRIGHT: (C)1993,JPO&Japio

